

# SUSPENSION AND STRAIN CLAMP

## ALUMINIUM STRAIN CLAMP

Strain Clamps are designed for use with AAC,AAAC, or ACSR Conductor

| Catalogue Number | Clamp Range mm | Rated Strength kN | Dimensions, mm |      |     |    |    | U-Bolts |          | Approx. Weight, kg |
|------------------|----------------|-------------------|----------------|------|-----|----|----|---------|----------|--------------------|
|                  |                |                   | A              | B    | C   | D  | E  | NO.     | Size, mm |                    |
| ATC-51114        | 5.1 ~ 11.4     | 40                | 108            | 19   | 126 | 20 | 16 | 2       | 12       | 0.5                |
| ATC-89185        | 8.9 ~ 18.5     | 40                | 187            | 24   | 176 | 32 | 16 | 2       | 12       | 1.8                |
| ATC-50150        | 5.0 ~ 15.0     | 70                | 203            | 17.5 | 190 | 20 | 16 | 3       | 12       | 1.9                |
| ATC-121218       | 12.1 ~ 21.8    | 70                | 284            | 30   | 298 | 32 | 16 | 4       | 12       | 4.1                |
| ATC-180300       | 18.0 ~ 30.0    | 70                | 342            | 36   | 446 | 38 | 20 | 5       | 12       | 7.0                |

**Material:**

Body and Keeper - Aluminium alloy

Hardware - Galvanized steel

Split pin - Stainless steel

