

# SUSPENSION AND STRAIN CLAMP

## ALUMINIUM SUSPENSION CLAMP

Aluminium Suspension Clamps are designed for use with AAC,AAAC and ACSR in suspension applications for deviation angles of up to 20 deg.

Catalogue Number	Clamp Range mm	Rated Strength kN	Dimensions, mm				Approx. Weight kg
			A	B	C	$\phi$	
ASC-5085	5 ~ 8.5	36	178	17.5	54	12	1.2
ASC-71130	7.1 ~ 13.0	36	190	18	54	12	1.4
ASC-110185	11.0 ~ 18.5	36	180	22	62	12	1.5
ASC-178235	17.8 ~ 23.5	36	226	28	74	12	2.3
ASC-230320	23.0 ~ 32.0	60	262	35	87	12	3.1
ASC-250350	25.0 ~ 35.0	60	262	38	87	12	3.5
ASC-270390	27.0 ~ 39.0	70	230	40	54	12	3.9
ASC-280412	28.0 ~ 41.2	70	241	43	78	12	4.5
ASC-356518	35.6 ~ 51.8	70	267	54	95	12	4.8
ASC-445572	44.5 ~ 57.2	70	280	58.7	95	16	5.1

**Material:**  
 Body and Keeper - Aluminium alloy  
 Hardware -Galvanized steel  
 Split Pin - Stainless steel

